

PvBlack X930B

特种炭黑 Special carbon black

简介 introduction:

特种炭黑 PvBlack X930B 设计用于工程塑胶、电线电缆、合成革、粉体涂料、化妆品等，还可用于汽车漆、高级金属装饰磁漆、黑色高级涂料。Special carbon black PvBlack X930B is designed for engineering plastics, wire and cable, synthetic leather, powder coatings, cosmetics, etc. It can also be used in automotive paint, high-grade metal decorative enamel, black high-grade paint.

理化性质 Physical and Chemical Properties	参数 parameter
外观 Appearance	粒状 granulous
平均原生粒径 Average original particle size (nm)	15±1
BET 比表面积 BET Specific surface area (m ² /g)	250±10
DBP 吸油值 DBP Oil Absorption (cc/100g)	55±5
相对着色, IRB#3(%) Tinting Strength	130±5
挥发份 Volatile matter (%)	0.3±1
PH 值	8.5±0.5

应用与特性 Application and characteristics:

- ◆ 高黑度 High blackness
- ◆ 蓝相 blue phase
- ◆ 高光泽 High gloss

推荐应用 Recommended application:

用于工程塑胶、通用色母、电线电缆、合成革、粉体涂料、化妆品、汽车漆、高级金属装饰磁漆、黑色高级涂料

For Engineering plastics, general color masterbatch, wire and cable, synthetic leather, powder coating, cosmetics, automotive paint, high-grade metal decorative enamel, black high-grade paint.

包装 packing: 20KG/Bag

备注: 本数据资料的提供出于诚意, 仅供参考, 需要由您自己测试并决定是否适合您的用途, 对我们产品的应用和处理以及您制造的最终产品都处于我们的控制之外, 我们无法承担保证和义务。

PS:The Data above is provided in good faith,FYI.

工厂地址: 新疆胡杨河市胡杨经济技术开发区车排子西路 3 号

公司地址: 东莞市常平镇桥沥南北路 25 号

电话: +86 (0) 755 23246611; 13510821649

传真: +86 (0) 755 29467129

邮箱: texong@163.com 网址: www.texong.com